

# Safe Operating Speeds

The maximum safe operating speeds for all M939-series 5-ton trucks have changed.

The information listed in Table 1-9A of TM 9-2320-272-10 is only for M939-series trucks that have not had the antilock brake system (ABS) added by MWO. Make sure that's noted in the table's title.

Then add a Table 1-9B for all M939-series trucks that have ABS installed by MWO—



Highway and secondary roads	55 mph
Cross country roads	35 mph
Mud, sand and snow	25 mph
Emergency (ice, extreme conditions)	5 mph

# TIRE PRESSURE CHANGES

The tire inflation data table in TM 9-2320-272-10 has changed.

For all basic model M939-series trucks except the M945, inflation pressure is:

Condition, Location	Pressure
Highway, front tires.....	65 psi
Highway, rear tires.....	50 psi
Cross-country, front tires.....	45 psi
Cross-country, rear tires.....	35 psi
Mud, sand and snow, front tires.....	40 psi
Mud, sand and snow, rear tires.....	30 psi
Emergency, front tires.....	30 psi
Emergency, rear tires.....	25 psi



The info on Page 1-25 in the -10 TM for M939A1-series and A2-series trucks is correct, but you need to add a column for the M945 and the M945A1.

Condition, Location	Pressure
Highway, front tires.....	75 psi
Highway, rear tires.....	30 psi
Cross-country, front tires.....	45 psi
Cross-country, rear tires.....	25 psi
Mud, snow and sand, front and rear tires.....	25 psi
Emergency, front and rear...	25 psi