

SEALING COMPOUNDS HOLD FAST



WHEN YOU NEED TO LOCK AND SEAL THREADED FASTENERS, APPLY SEALING COMPOUND.

IT'LL HOLD THEM TIGHT.



THE COMPOUND COMES IN VARYING STRENGTHS AND FOR ALL KINDS OF APPLICATIONS. THE TABLE BELOW SPELLS OUT THE SIZES, USES AND FEATURES.

USE THIS CHART TO FIND THE COMPOUND YOU NEED!

NSN 8030-	Size	Typical Use	Color	Breaking Torque (lb-in)	Holding Torque (lb-in)	Initial Set (minutes)
01-054-3968	Ten 10-cc bottles	Small screws under 3/4-in	Purple	53	30	20
01-069-3046	50-cc bottle	Small screws under 3/4-in	Purple	53	30	20
01-104-5392	Ten 10-cc bottles	Up to 3/4-in bolts (removable lock)	Blue	115	53	10
01-014-5869	50-cc bottle	Up to 3/4-in bolts (removable lock)	Blue	115	53	10
01-025-1692	250-cc bottle	Up to 3/4-in bolts (removable lock)	Blue	115	53	10
01-142-9830	Ten 50-ml bottles	Up to 3/4-in bolts (permanent lock)	Red	190	275	20
01-142-3131	250-cc bottle	Up to 3/4-in bolts (permanent lock)	Red	190	275	20
01-171-7628	50-ml bottle	High temperature applications	Red	200	220	30
00-111-2763	Ten 10-cc bottles	Wicking grade for preassembled parts	Green	85	250	20
00-111-2762	50-cc bottle	Wicking grade for preassembled parts	Green	85	250	20
01-050-8288	250-cc bottle	Wicking grade for preassembled parts	Green	85	250	20
01-390-7555	20-gram bottle	Small plastic fasteners	Blue	5	4	2